



Military-Fasteners.com

P/N MS35266-27

Description

Fastener Length: 5/16", Hole Diameter: 1/32", Thread: 6-40, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3526627
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-145-0944
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35266-27 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.231 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.208 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.089 Inches Minimum And 0.096 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.138 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010 Or Steel Comp 1015 Or Steel Comp 1016 Or Steel Comp 1018 Or Steel Comp 1019 Or Steel Comp 1020 Or Steel Comp 1022 Or Steel Comp 1025 Or Steel Comp 1026 Or Steel Comp 1035 Or Steel Comp 1040 Or Steel Comp 1042 Or Steel Comp 1045 Or Steel Comp 1046 Or Steel Comp 1548 Or Steel Comp 1049 Or Steel Comp 1050 Or Steel
Screw Surface Treatment:	Cadmium Or Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses
Head Hole Configuration Style:	Round
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 5s Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35266-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.