

Description

Fastener Length: 5/16", Hole Diameter: 1/32", Thread: 8-36, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3526642
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-588-7669
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS35266-42 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.256 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.250 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.106 Inches Minimum And 0.113 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-633 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,c1 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35266-42> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.