

Description

Length: 3/4", thread: 10-32, fillister head machine screw, cadmium plated carbon steel, fine thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3526665
Minimum Qty (MOQ):	50
NSN:	5305-00-616-4831
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35266-65 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.688 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.750 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.292 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.123 Inches Minimum And 0.130 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-633 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35266-65> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.