

Description

Length: 5/16", Hole Diameter: ", Thread: 1/4-28, Thread Length: 5/16", drilled head, MS35266 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS3526676 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-00-866-0444 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS35266-76 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.241 Inches Minimum And 0.312 Inches Maximum |
| Fastener Length: | 0.281 Inches Minimum And 0.312 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.389 Inches Minimum And 0.414 Inches Maximum |
| Head Height: | 0.161 Inches Minimum And 0.170 Inches Maximum |
| Hole Diameter: | 0.062 Inches Nominal |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Hole Quantity: | 1 |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Qq-s-633 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses |
| Head Hole Configuration Style: | Round |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35266-76> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.