

**Description**

Fastener Length: 5/16", Hole Diameter: 1/32", Thread: 4-40, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS3527314
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-828-7658
Schedule B:	7415.33.8050
ECCN:	9A991
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



\* See page 2 for technical characteristics

## P/N MS35273-14 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.262 Inches Minimum And 0.312 Inches Maximum
<b>Fastener Length:</b>	0.281 Inches Minimum And 0.312 Inches Maximum
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.166 Inches Minimum And 0.183 Inches Maximum
<b>Head Height:</b>	0.072 Inches Minimum And 0.079 Inches Maximum
<b>Hole Diameter:</b>	0.037 Inches Nominal
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Hole Quantity:</b>	1
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	57000 Pounds Per Square Inch
<b>Screw Material:</b>	Copper Alloy
<b>Screw Material Document And Classification:</b>	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
<b>Head Hole Configuration Style:</b>	Round
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35273-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.