

Description

Fastener Length: 11/32", Hole Diameter: 3/64", Thread: 8-32, Thread Length: 19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS3527343 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-226-7221 |
| Schedule B: | 7415.33.8050 |
| ECCN: | EAR99 |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |

NO IMAGE
AVAILABLE

P/N MS35273-43 Specifications

| | |
|--|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.282 Inches Minimum And 0.375 Inches Maximum |
| Fastener Length: | 0.344 Inches Minimum And 0.375 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.250 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.106 Inches Minimum And 0.113 Inches Maximum |
| Hole Diameter: | 0.046 Inches Nominal |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.164 Inches |
| Hole Quantity: | 1 |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 57000 Pounds Per Square Inch |
| Screw Material: | Copper Alloy |
| Screw Material Document And Classification: | Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response |
| Head Hole Configuration Style: | Round |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35273-43> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.