

Description

Fastener Length: 7/8", Hole Diameter: 3/64", Thread: 8-32, Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3527348
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-226-7225
Schedule B:	7415.33.8050
ECCN:	9A991
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE
AVAILABLE

P/N MS35273-48 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.813 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	0.875 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.250 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.106 Inches Minimum And 0.113 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Screw Material:	Copper Alloy
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35273-48> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.