



Military-Fasteners.com

P/N MS35273-49

## Description

Fastener Length: 1-", Hole Diameter: 1/32", Thread: 8-32, Thread Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS3527349
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-226-7226
Schedule B:	7415.33.8000
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



\* See page 2 for technical characteristics

## P/N MS35273-49 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.938 Inches Minimum And 1.000 Inches Maximum
<b>Fastener Length:</b>	1.000 Inches Nominal
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.250 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.106 Inches Minimum And 0.113 Inches Maximum
<b>Hole Diameter:</b>	0.046 Inches Nominal
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Hole Quantity:</b>	1
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	57000 Pounds Per Square Inch
<b>Screw Material:</b>	Copper Alloy
<b>Screw Material Document And Classification:</b>	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response
<b>Head Hole Configuration Style:</b>	Round
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35273-49> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.