



Military-Fasteners.com

P/N MS35274-34

Description

Fastener Length: 1-", Hole Diameter: 1/32", Thread: 6-40, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3527434
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-939-0681
Schedule B:	7415.33.8050
ECCN:	9A991
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



* See page 2 for technical characteristics

P/N MS35274-34 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.950 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.208 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.089 Inches Minimum And 0.096 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.138 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	57000 Pounds Per Square Inch
Screw Material:	Copper Alloy 230 Or Copper Alloy 240 Or Copper Alloy 260 Or Copper Alloy 268 Or Copper Alloy 270 Or Copper Alloy 342 Or Copper Alloy 353 Or Copper Alloy 360 Or Copper Alloy 377 Or Copper Alloy 510 Or Copper Alloy 745 Or Copper Alloy 752 Or Copper Alloy 764 Or Copper Alloy 770
Head Hole Configuration Style:	Round
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35274-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.