

**Description**

Fastener Length: 3/16", Thread: 2-56, Thread Length: 3/16", drilled head, MS35275 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS35275202
Minimum Qty (MOQ):	50
NSN:	5305-00-922-8777
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS35275-202 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.188 Inches Minimum
<b>Fastener Length:</b>	0.188 Inches Nominal
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.124 Inches Minimum And 0.140 Inches Maximum
<b>Head Height:</b>	0.055 Inches Minimum And 0.062 Inches Maximum
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Thread Quantity Per Inch:</b>	56
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
<b>Screw Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35275-202> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.