

Description

MS35275-203 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS35275203 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-922-8778 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS35275-203 Specifications

| | |
|---------------------------------------|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.250 Inches Maximum |
| Fastener Length: | 0.250 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.124 Inches Minimum And 0.140 Inches Maximum |
| Head Height: | 0.055 Inches Minimum And 0.062 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.086 Inches |
| Thread Quantity Per Inch: | 56 |
| Screw Material: | Steel Corrosion Resisting |
| Screw Surface Treatment: | Passivate |
| Test Data Document: | 81348-ffs92 Specification (includes Engineering Type Bulletins, Brochures, etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.). |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 1 Type And 5s Style |
| Departure From Cited Document: | As Modified By Material |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35275-203> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.