

P/N MS35275-208

Description

Fastener Length: 5/8", Hole Diameter: ", Thread: 2-56, Thread Length: 5/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS35275208

Minimum Qty (MOQ): 25

NSN: 5305-00-941-6403

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS35275-208 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Minimum
Fastener Length:	0.625 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.124 Inches Minimum And 0.140 Inches Maximum
Head Height:	0.055 Inches Minimum And 0.062 Inches Maximum
Hole Diameter:	0.031 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.086 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS35275-208 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.