

Description

length: 5/16", thread: 6-32, fillister head, corrosion resistant steel, coarse thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS35275227 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-940-9489 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS35275-227 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.250 Inches Minimum And 0.312 Inches Maximum |
| Fastener Length: | 0.281 Inches Minimum And 0.312 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.208 Inches Minimum And 0.226 Inches Maximum |
| Head Height: | 0.089 Inches Minimum And 0.096 Inches Maximum |
| Hole Diameter: | 0.046 Inches Nominal |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.138 Inches |
| Hole Quantity: | 1 |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Screw Material: | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 |
| Screw Material Document And Classification: | 66 Fed Std All Material Responses |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Head Hole Configuration Style: | Round |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35275-227> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.