

## P/N MS35275-241

## **Description**

Fastener Length: 1/4", Hole Diameter: 1/32", Thread: 8-32, Thread Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS35275241

Minimum Qty (MOQ): 50

NSN: 5305-00-939-9221

EAR99 ECCN:

093486, Bolts, nuts Or Screws, Noi (sub 3) National Motor Freight:











<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35275-241 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.188 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.250 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.106 Inches Minimum And 0.113 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS35275-241">https://military-fasteners.com/screws/machine+screws/MS35275-241</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.