



Military-Fasteners.com

P/N MS35275-249

Description

Fastener Length: 1", Hole Diameter: 1/32", Thread: 8-32, Thread Length: 63/64", drilled, MS35275 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35275249
Minimum Qty (MOQ):	50
NSN:	5305-00-943-5918
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35275-249 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.938 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.250 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.106 Inches Minimum And 0.113 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35275-249> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.