

P/N MS35275-287

Military-Fasteners.com

Description

Fastener Length: 2", Thread: 1/4-20, Thread Length: 1-63/64", MS35275 series screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS35275287
Minimum Qty (MOQ):	5
NSN:	5305-00-939-9172
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



P/N MS35275-287 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.900 Inches Minimum And 2.000 Inches Maximum
Fastener Length:	2.000 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.389 Inches Minimum And 0.414 Inches Maximum
Head Height:	0.161 Inches Minimum And 0.170 Inches Maximum
Hole Diameter:	0.062 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS35275-287</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.