

P/N MS35276-212

Description

Fastener Length: 1/8", Hole Diameter: ", Thread: 4-48, Thread Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS35276212

Minimum Qty (MOQ): 5

NSN: 5305-00-914-3809

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



P/N MS35276-212 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.187 Inches Minimum
Fastener Length:	0.187 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.166 Inches Minimum And 0.183 Inches Maximum
Head Height:	0.072 Inches Minimum And 0.079 Inches Maximum
Hole Diameter:	0.031 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.112 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	48
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	66 Fed Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS35276-212 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.