

Description

Fastener Length: 1/8", Hole Diameter: ", Thread: 4-48, Thread Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS35276212 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-00-914-3809 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS35276-212 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.187 Inches Minimum |
| Fastener Length: | 0.187 Inches Nominal |
| Head Style: | Fillister |
| Head Diameter: | 0.166 Inches Minimum And 0.183 Inches Maximum |
| Head Height: | 0.072 Inches Minimum And 0.079 Inches Maximum |
| Hole Diameter: | 0.031 Inches Nominal |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.112 Inches |
| Hole Quantity: | 1 |
| Thread Quantity Per Inch: | 48 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Screw Material: | Steel Corrosion Resisting |
| Screw Material Document And Classification: | 66 Fed Std Single Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Head Hole Configuration Style: | Round |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35276-212> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.