



Military-Fasteners.com

P/N MS35276-262

Description

Fastener Length: 7/16", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35276262
Minimum Qty (MOQ):	50 EA
NSN:	5305-00-912-4839
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS35276-262 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.376 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.438 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.292 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.123 Inches Minimum And 0.130 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35276-262> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.