

Description

length: 1.25", thread: 1/4-20,

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS35307310 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-021-3668 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS35307-310 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.750 Inches Minimum And 0.938 Inches Maximum |
| Fastener Length: | 1.250 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.150 Inches Minimum And 0.163 Inches Maximum |
| Width Between Flats: | 0.428 Inches Minimum And 0.438 Inches Maximum |
| End Item Identification: | Mrap Buffalo Mk2a2 |
| End Item Identification: | Mrap Buffalo Mk2a2;mrap - M-atv With Cs13 Pop And Sne |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Material: | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this hexagon head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/hexagon+head+cap+screws/MS35307-310> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.