

# P/N MS35307-329

## **Description**

Fastener Length: 1/2", Thread: 1/4-18, Thread Length: 15/32", MS35307 series screw

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS35307329

Minimum Qty (MOQ): 25

NSN: 5306-00-807-1213

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35307-329 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.303 Inches Minimum And 0.469 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Hexagon
Head Height:	0.195 Inches Minimum And 0.211 Inches Maximum
Width Between Flats:	0.489 Inches Minimum And 0.500 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	85000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw,cap,hexagon Head
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

## **How to Order**

Order this hexagon head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/hexagon+head+cap+screws/MS35307-329">https://military-fasteners.com/screws/hexagon+head+cap+screws/MS35307-329</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.