

P/N MS35307-360

Military-Fasteners.com

Description

MS35307-360 Hexagon Head Cap Screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS35307360
Minimum Qty (MOQ):	10
NSN:	5305-00-576-5417
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS35307-360 Specifications

Thread Direction:Right-handThread Direction:Right-handFastener Length:0.813 Inches Minimum And 0.844 Inches MaximumFastener Length:0.969 Inches Minimum And 1.000 Inches MaximumHead Style:HexagonHead Height:0.226 Inches Minimum And 0.243 Inches MaximumWidth Between Flats:0.551 Inches Minimum And 0.562 Inches MaximumEnd Item Identification:0.375 Inches Minimum And 0.562 Inches MaximumMinimum Tensile Strength:0.375 InchesNominal Thread Diameter:0.375 InchesMinimum Tensile Strength:80000 Pounds Per Square InchMaterial Document And Classification:66 Fed Stq Single Material Response OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Pasivate OverallSurface Treatment Document And0.975 Fed Spec Single Treatment Response Overall		
Thread Length:0.813 Inches Minimum And 0.844 Inches MaximumFastener Length:0.969 Inches Minimum And 1.000 Inches MaximumHead Style:HexagonHead Height:0.226 Inches Minimum And 0.243 Inches MaximumWidth Between Flats:0.551 Inches Minimum And 0.562 Inches MaximumEnd Item Identification:0.551 Inches Minimum And 0.562 Inches MaximumKk2a2Nominal Thread Diameter:0.375 InchesNominal Thread Diameter:0.375 InchesBinimum Tensile Strength:80000 Pounds Per Square InchMinimum Yield Strength:30000 Pounds Per Square InchMaterialSteel Corrosion Resisting OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment Document AndQa-p-35 Fed Spec Single Treatment Response Overall	Thread Class:	2a
Fastener Length:0.969 Inches Minimum And 1.000 Inches MaximumHead Style:HexagonHead Height:0.226 Inches Minimum And 0.243 Inches MaximumWidth Between Flats:0.551 Inches Minimum And 0.562 Inches MaximumEnd Item Identification:3330-01-537-8217, Semitrailer, Tank, 5000 Gallon, Fuel Dispensing, Under/overwing Aircraft; Rg-33 Mrap; Mrap Buffalo Mk2a2Nominal Thread Diameter:0.375 InchesThread Quantity Per Inch:16Minimum Tensile Strength:8000 Pounds Per Square InchMinimum Yield Strength:8000 Pounds Per Square InchMaterial:Stoel Corrosion Resisting OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment Document And Classification:ap-35 Fed Spec Single Treatment Response Overall	Thread Direction:	Right-hand
Head Style:HexagonHead Height:0.226 Inches Minimum And 0.243 Inches MaximumWidth Between Flats:0.551 Inches Minimum And 0.562 Inches MaximumEnd Item Identification:2330-01-537-8217, Semitrailer, Tank, 5000 Gallon, Fuel Dispensing, Under/overwing Aircraft; Rg-33 Mrap; Mrap Buffalo Mk2a2Nominal Thread Diameter:0.375 InchesThread Quantity Per Inch:16Minimum Tensile Strength:8000 Pounds Per Square InchMarcraft:80.00 Pounds Per Square InchMaterial:Steel Corrosion Resisting OverallMaterial:Steel Corrosion Resisting OverallMaterial:66 Fed Std Single Material Response OverallSurface Treatment:Pasivate OverallSurface Treatment Document And Classification:Q-p-35 Fed Spec Single Treatment Response Overall	Thread Length:	0.813 Inches Minimum And 0.844 Inches Maximum
Head Height:0.226 Inches Minimum And 0.243 Inches MaximumWidth Between Flats:0.551 Inches Minimum And 0.562 Inches MaximumEnd Item Identification:2330-01-537-8217, Semitrailer, Tank, 5000 Gallon, Fuel Dispensing, Under/overwing Aircraft; Rg-33 Mrap; Mrap Buffalo Mk2a2Nominal Thread Diameter:0.375 InchesOntread Quantity Per Inch:16Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Corrosion Resisting OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Passivate OverallQr.p-35 Fed Spec Single Treatment Response Overall	Fastener Length:	0.969 Inches Minimum And 1.000 Inches Maximum
Width Between Flats:0.551 Inches Minimum And 0.562 Inches MaximumEnd Item Identification:330-01-537-8217, Semitrailer, Tank, 5000 Gallon, Fuel Dispensing, Under/overwing Aircraft; Rg-33 Mrap; Mrap Buffalo Mk2a2Nominal Thread Diameter:0.375 InchesThread Quantity Per Inch:16Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.000 Pounds Per Square InchMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Corrosion Resisting OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Passivate OverallQuep-35 Fed Spec Single Treatment Response Overall	Head Style:	Hexagon
End Item Identification:2330-01-537-8217, Semitrailer, Tank, 5000 Gallon, Fuel Dispensing, Under/overwing Aircraft; Rg-33 Mrap; Mrap Buffalo Mk2a2Nominal Thread Diameter:0.375 InchesThread Quantity Per Inch:16Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.00 Pounds Per Square InchMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Corrosion Resisting OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Q-p-35 Fed Spec Single Treatment Response Overall	Head Height:	0.226 Inches Minimum And 0.243 Inches Maximum
End Item Identification:Mk2a2Nominal Thread Diameter:0.375 InchesThread Quantity Per Inch:16Minimum Tensile Strength:80000 Pounds Per Square InchMardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Corrosion Resisting OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:operationQuep-35 Fed Spec Single Treatment Response Overall	Width Between Flats:	0.551 Inches Minimum And 0.562 Inches Maximum
Thread Quantity Per Inch:16Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Corrosion Resisting OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment:Passivate OverallQuep-35 Fed Spec Single Treatment Response Overall	End Item Identification:	
Minimum Tensile Strength:80000 Pounds Per Square InchHardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Corrosion Resisting OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.375 Inches
Hardness Rating:80.0 Rockwell B Minimum OverallMinimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Corrosion Resisting OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	16
Minimum Yield Strength:30000 Pounds Per Square InchMaterial:Steel Corrosion Resisting OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	80000 Pounds Per Square Inch
Material:Steel Corrosion Resisting OverallMaterial Document And Classification:66 Fed Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response Overall	Hardness Rating:	80.0 Rockwell B Minimum Overall
Material Document And Classification: 66 Fed Std Single Material Response Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Minimum Yield Strength:	30000 Pounds Per Square Inch
Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Material:	Steel Corrosion Resisting Overall
Surface Treatment Document And Qq-p-35 Fed Spec Single Treatment Response Overall Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Material Document And Classification:	66 Fed Std Single Material Response Overall
Classification: Qq-p-35 Fed Spec Single Treatment Response Overall	Surface Treatment:	Passivate Overall
	Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Inread Series Designator: Onc	Thread Series Designator:	Unc

How to Order

Order this hexagon head cap screw from our inventory online by visiting <u>https://military-fasteners.com/screws/hexagon+head+cap+screws/MS35307-360</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.