

Description

length: 1.25", hex head

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS35307362 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-717-5467 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS35307-362 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.000 Inches Minimum And 1.187 Inches Maximum |
| Fastener Length: | 1.250 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.226 Inches Minimum And 0.243 Inches Maximum |
| Width Between Flats: | 0.551 Inches Minimum And 0.562 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Thread Quantity Per Inch: | 16 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Material: | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this hexagon head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/hexagon+head+cap+screws/MS35307-362> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.