

## P/N MS35307-398

### **Description**

Fastener Length: 3-3/4", Thread: 7/16-14, Thread Length: 1-5/16

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS35307398
Minimum Qty (MOQ):	5
NSN:	5305-01-225-3578
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35307-398 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.126 Inches Minimum And 1.314 Inches Maximum
Fastener Length:	3.656 Inches Minimum And 3.750 Inches Maximum
Head Style:	Hexagon
Head Height:	0.272 Inches Minimum And 0.291 Inches Maximum
Width Between Flats:	0.612 Inches Minimum And 0.625 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 302b Overall Or Steel Comp 303 Overall Or Steel Comp 303se Overall Or Steel Comp 304 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 308 Overall Or Steel Comp 309 Overall Or Steel Comp 310 Overall Or Steel Comp 311 Overall Or Steel Comp 312 Overall Or Steel Comp 313 Overall Or Steel Comp 314 Overall Or Steel Comp 315 Overall Or Steel Comp 315 Overall Or Steel Comp 315 Overall Or Steel Comp 316 Overall Or Steel Comp 316 Overall Or Steel Comp 317 Overall Or Steel Comp 317 Overall Or Steel Comp 318
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	2 Type And 10p Style

# **How to Order**

