

## P/N MS35308-341

### **Description**

Fastener Length: 2-1/4", Thread: 1/4-24, Thread Length: 7/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS35308341

Minimum Qty (MOQ): 15 EA

NSN: 5306-00-080-0680

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35308-341 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Minimum
Fastener Length:	2.156 Inches Minimum And 2.250 Inches Maximum
Head Style:	Hexagon
Head Height:	0.195 Inches Minimum And 0.211 Inches Maximum
Width Between Flats:	0.489 Inches Minimum And 0.500 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.281 Inches Minimum And 1.375 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 303f Overall Or Steel Comp 303se Overall Or Steel Comp 304 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 308 Overall Or Steel Comp 309 Overall Or Steel Comp 310 Overall Or Steel Comp 321 Overall Or Steel Comp 323 Overall Or Steel Comp 324 Overall Or Steel Comp 348 Overall Or Steel Comp 314 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/MS35308-341">https://military-fasteners.com/bolts/machine+bolts/MS35308-341</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.