

P/N MS35308-358

Description

Fastener Length: 3/4", Thread: 3/8-24, Thread Length: 3/4", hex head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS35308358

Minimum Qty (MOQ): 20

NSN: 5305-00-059-3524

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N MS35308-358 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Maximum
Fastener Length:	0.750 Inches Nominal
Head Height:	0.226 Inches Minimum And 0.243 Inches Maximum
Width Between Flats:	0.551 Inches Minimum And 0.562 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS35308-358 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/MS35308-358 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/MS35308-358 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/MS35308-358 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+bolts/machine+