

**Description**

Fastener Length: 7/8", Thread: 3/8-24, Thread Length: 7/8",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS35308359
Minimum Qty (MOQ):	20
NSN:	5305-00-754-3104
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS35308-359 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.875 Inches Maximum
<b>Fastener Length:</b>	0.875 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.226 Inches Minimum And 0.243 Inches Maximum
<b>Width Between Flats:</b>	0.551 Inches Minimum And 0.562 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS35308-359> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.