

P/N MS35309-360

Description

Fastener Length: 0-63/64", Thread: 3/8-16, Thread Length: 1-1/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS35309360

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-004-7111

Schedule B: 7415.33.8050

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper



^{*} See page 2 for technical characteristics

P/N MS35309-360 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.000 Inches Maximum
Fastener Length:	0.970 Inches Minimum And 1.000 Inches Maximum
Head Style:	Hexagon
Head Height:	0.226 Inches Minimum And 0.243 Inches Maximum
Width Between Flats:	0.551 Inches Minimum And 0.563 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Minimum Yield Strength:	27000 Pounds Per Square Inch
Surface Finish:	63.0 Microinches Threads
Material:	Copper Alloy 462 Overall Or Copper Alloy 464 Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	2 Type And 10p Style

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS35309-360 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS35309-360 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS35309-360 and selecting the quantity you want then click "add to cart".