

**Description**

Fastener Length: 0-63/64", Thread: 3/8-16, Thread Length: 1-1/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS35309360
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-004-7111
Schedule B:	7415.33.8050
ECCN:	EAR99
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE  
AVAILABLE

## P/N MS35309-360 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.000 Inches Maximum
<b>Fastener Length:</b>	0.970 Inches Minimum And 1.000 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.226 Inches Minimum And 0.243 Inches Maximum
<b>Width Between Flats:</b>	0.551 Inches Minimum And 0.563 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Thread Quantity Per Inch:</b>	16
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Minimum Yield Strength:</b>	27000 Pounds Per Square Inch
<b>Surface Finish:</b>	63.0 Microinches Threads
<b>Material:</b>	Copper Alloy 462 Overall Or Copper Alloy 464 Overall
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	2 Type And 10p Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS35309-360> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.