

## P/N MS35333-105

## **Description**

diameter: #6, brass or bronze, MS35333 series washer

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS35333105

Minimum Qty (MOQ): 100

NSN: 5310-00-019-0669

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35333-105 Specifications

Hole Diameter:	0.141 Inches Minimum And 0.150 Inches Maximum
Outside Diameter:	0.275 Inches Minimum And 0.295 Inches Maximum
Material Thickness:	0.017 Inches Minimum And 0.021 Inches Maximum
Material:	Copper Alloy Overall
Material Document And Classification:	Qq-b-750 Fed Spec Single Material Response Overall
Style Designator:	Flat Internal Teeth
Nondefinitive Spec/std Data:	A Type

### **How to Order**

Order this lock washer from our inventory online by visiting <a href="https://military-fasteners.com/washers/lock+washers/MS35333-105">https://military-fasteners.com/washers/lock+washers/MS35333-105</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/washers/lock+washers/MS35333-105">https://military-fasteners.com/washers/lock+washers/MS35333-105</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/washers/lock+washers/MS35333-105">https://military-fasteners.com/washers/lock+washers/MS35333-105</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/washers/MS35333-105">https://military-fasteners.com/washers/lock+washers/MS35333-105</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/washers/MS35333-105">https://military-fasteners.com/washers/MS35333-105</a> and selecting the property of the