

Description

Hole Diameter: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35333125
Minimum Qty (MOQ):	100
NSN:	5310-01-142-0326
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N MS35333-125 Specifications

Hole Diameter:	0.256 Inches Minimum And 0.267 Inches Maximum
Outside Diameter:	0.395 Inches Minimum And 0.410 Inches Maximum
Material Thickness:	0.016 Inches Minimum And 0.020 Inches Maximum
Material:	Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1552 Overall Or Steel Comp 1053 Overall Or Steel Comp 1055 Overall Or Steel Comp 1059 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1064 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	Flat Internal Teeth
Nondefinitive Spec/std Data:	1 Type And A Grade And 1 Composition

How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-125> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.