

**Description**

Hole Diameter: 3/8",

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS35333134
Minimum Qty (MOQ):	50
NSN:	5310-01-147-2448
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE  
AVAILABLE

## P/N MS35333-134 Specifications

<b>Hole Diameter:</b>	0.383 Inches Minimum And 0.392 Inches Maximum
<b>Outside Diameter:</b>	0.493 Inches Minimum And 0.507 Inches Maximum
<b>Material Thickness:</b>	0.020 Inches Minimum And 0.030 Inches Maximum
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
<b>Material:</b>	Steel Comp 410 Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35,type 2 Or Type 3 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Flat Internal Teeth
<b>Nondefinitive Spec/std Data:</b>	1 Type And 2 Style And 2 Composition

## How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-134> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.