

Description

Hole Diameter: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS35333134
Minimum Qty (MOQ):	50
NSN:	5310-01-147-2448
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



NO IMAGE
AVAILABLE

P/N MS35333-134 Specifications

Hole Diameter:	0.383 Inches Minimum And 0.392 Inches Maximum
Outside Diameter:	0.493 Inches Minimum And 0.507 Inches Maximum
Material Thickness:	0.020 Inches Minimum And 0.030 Inches Maximum
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,type 2 Or Type 3 Fed Spec Single Treatment Response Overall
Style Designator:	Flat Internal Teeth
Nondefinitive Spec/std Data:	1 Type And 2 Style And 2 Composition

How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-134> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.