

Description

Hole Diameter: 1/4", internal teeth, MS35333 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS35333135
Minimum Qty (MOQ):	50
NSN:	5310-01-078-2992
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE
AVAILABLE

P/N MS35333-135 Specifications

Hole Diameter:	0.256 Inches Minimum And 0.267 Inches Maximum
Outside Diameter:	0.395 Inches Minimum And 0.410 Inches Maximum
Material Thickness:	0.016 Inches Minimum And 0.020 Inches Maximum
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Material:	Steel Comp 410 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,type 2 Fed Spec Single Treatment Response Overall Or Qq-p-35,type 3 Fed Spec Single Treatment Response Overall
Style Designator:	Flat Internal Teeth
Nondefinitive Spec/std Data:	3 Type And 2 Composition

How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-135> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.