

P/N MS35333-136

Description

Hole Diameter: 1/2", MS35333 series washer

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS35333136

Minimum Qty (MOQ): 25

NSN: 5310-01-078-9699

Schedule B: 7318.22.0000

ECCN: EAR99

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,









^{*} See page 2 for technical characteristics

P/N MS35333-136 Specifications

Hole Diameter:	0.472 Inches Minimum And 0.480 Inches Maximum
Outside Diameter:	0.593 Inches Minimum And 0.607 Inches Maximum
Material Thickness:	0.013 Inches Minimum And 0.023 Inches Maximum
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall And Qq-p-35,ty 3 Fed Spec Single Treatment Response Overall
Style Designator:	Flat Internal Teeth
Nondefinitive Spec/std Data:	1 Type And A Grade And 1 Style And 2 Composition

How to Order

Order this lock washer from our inventory online by visiting https://military-fasteners.com/washers/lock+washers/MS35333-136 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/lock+washers/MS35333-136 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/lock+washers/MS35333-136 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/MS35333-136 and selecting the quantity you want https://military-fasteners.com/washers/MS35333-136 and selecting the property of the prope