

Description

Hole Diameter: 5/8", MS35333 series washer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS35333138 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-01-074-7463 |
| Schedule B: | 7318.22.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



P/N MS35333-138 Specifications

| | |
|---|--|
| Hole Diameter: | 0.630 Inches Minimum And 0.640 Inches Maximum |
| Outside Diameter: | 0.790 Inches Minimum And 0.800 Inches Maximum |
| Material Thickness: | 0.017 Inches Minimum And 0.027 Inches Maximum |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Ty 2 Fed Spec Single Treatment Response Overall Or Qq-p-35 Ty 3 Fed Spec Single Treatment Response Overall |
| Style Designator: | Flat Internal Teeth |
| Nondefinitive Spec/std Data: | 1 Type And A Grade |

How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-138> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.