

**Description**

Hole Diameter: 1-3/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS3533332
Minimum Qty (MOQ):	15 EA
NSN:	5310-00-013-8572
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE  
AVAILABLE

## P/N MS35333-32 Specifications

<b>Hole Diameter:</b>	1.019 Inches Minimum And 1.060 Inches Maximum
<b>Outside Diameter:</b>	1.590 Inches Minimum And 1.637 Inches Maximum
<b>Material Thickness:</b>	0.059 Inches Minimum And 0.067 Inches Maximum
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Flat Internal Teeth
<b>Nondefinitive Spec/std Data:</b>	A Type

## How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.