

Description

Hole Diameter: 1-3/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS3533332 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5310-00-013-8572 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |

NO IMAGE
AVAILABLE

P/N MS35333-32 Specifications

| | |
|---|---|
| Hole Diameter: | 1.019 Inches Minimum And 1.060 Inches Maximum |
| Outside Diameter: | 1.590 Inches Minimum And 1.637 Inches Maximum |
| Material Thickness: | 0.059 Inches Minimum And 0.067 Inches Maximum |
| Hardness Rating: | 40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Style Designator: | Flat Internal Teeth |
| Nondefinitive Spec/std Data: | A Type |

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.