

## Description

Hole Diameter: 1/8",size: 2, internal teeth, MS35333 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS3533335
Minimum Qty (MOQ):	100
NSN:	5310-00-579-5554
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



## P/N MS35333-35 Specifications

<b>Hole Diameter:</b>	0.089 Inches Minimum And 0.095 Inches Maximum
<b>Outside Diameter:</b>	0.175 Inches Minimum And 0.200 Inches Maximum
<b>Material Thickness:</b>	0.010 Inches Minimum And 0.015 Inches Maximum
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
<b>Material:</b>	Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1059 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1064 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Flat Internal Teeth
<b>Nondefinitive Spec/std Data:</b>	A Type

## How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.