

Description


Hole Diameter: 1/8",size: 2, internal teeth, MS35333 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3533335
Minimum Qty (MOQ):	100
NSN:	5310-00-579-5554
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N MS35333-35 Specifications

Hole Diameter:	0.089 Inches Minimum And 0.095 Inches Maximum
Outside Diameter:	0.175 Inches Minimum And 0.200 Inches Maximum
Material Thickness:	0.010 Inches Minimum And 0.015 Inches Maximum
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Material:	Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1059 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1064 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Flat Internal Teeth
Nondefinitive Spec/std Data:	A Type

How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.