

Description

Hole Diameter: 3/8", MS35333 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3533342
Minimum Qty (MOQ):	100
NSN:	5310-00-595-7237
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N MS35333-42 Specifications

Hole Diameter:	0.384 Inches Minimum And 0.398 Inches Maximum
Outside Diameter:	0.670 Inches Minimum And 0.692 Inches Maximum
Material Thickness:	0.032 Inches Minimum And 0.040 Inches Maximum
End Item Identification:	Mrap Rg-33
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Material:	Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1059 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1064 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Nas-90725 National Std/spec Single Treatment Response Overall
Style Designator:	Flat Internal Teeth

How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-42> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.