



P/N MS35333-43

Military-Fasteners.com

Description

Hole Diameter: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3533343
Minimum Qty (MOQ):	100
NSN:	5310-00-685-3228
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N MS35333-43 Specifications

Hole Diameter:	0.448 Inches Minimum And 0.464 Inches Maximum
Outside Diameter:	0.740 Inches Minimum And 0.789 Inches Maximum
Material Thickness:	0.032 Inches Minimum And 0.040 Inches Maximum
End Item Identification:	W/s:truck, Heavy Expanded Mobility Tactical (hemtt); M1a2 Abrams Tank, 2350-01-328-5964 (eaa Cmbt85pk3); Missile, Advanced Medium Range Air-to-air (amraam)/aim120a; Support Equipment, B-1 Aircraft; Aircraft, C-18a, Ec-18b; Helicopter Landing System, Lamps Mk Iii; Smoke Generator Set, M157a2; Radar Set, An/pps-5b; Armored Security Vehicle, Model Xm1117; Tactical Air Opns Module (an/tyq-(23))
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Material:	Steel Comp 1060 Overall Or Steel Comp 1070 Overall Or Steel Comp 1078 Overall Or Steel Comp 1080 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Flat Internal Teeth
Nondefinitive Spec/std Data:	1 Type And A Grade And 1 Style And 1 Composition

How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-43> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.