

# P/N MS35333-46

## **Description**

Hole Diameter: 5/8", Cadmium

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS3533346

Minimum Qty (MOQ): 50

NSN: 5310-00-543-4385

ECCN: EAR99

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS35333-46 Specifications

Hole Diameter:	0.640 Inches Minimum And 0.663 Inches Maximum
Outside Diameter:	1.045 Inches Minimum And 1.071 Inches Maximum
Material Thickness:	0.042 Inches Minimum And 0.050 Inches Maximum
End Item Identification:	Gairborne Mobile Dir Air Spt Ct;fire Pumps;radar Set, Firefinder (an/tpq-;armored Security Vehicle;truck, Fire/crash P19;truck, Fire/crash P15;landing Craft,utility,115ft;helicopter, Carrier Based Asw
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Material:	Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1059 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1064 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Flat Internal Teeth
Nondefinitive Spec/std Data:	1 Type And A Grade And 1 Style And 1 Composition

### **How to Order**

Order this lock washer from our inventory online by visiting <a href="https://military-fasteners.com/washers/lock+washers/MS35333-46">https://military-fasteners.com/washers/lock+washers/MS35333-46</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.