

Description

Hole Diameter: 1-3/64", MS35333 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS3533349 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5310-00-582-6714 |
| Schedule B: | 7318.22.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



* See page 2 for technical characteristics

P/N MS35333-49 Specifications

| | |
|---|--|
| Hole Diameter: | 1.019 Inches Minimum And 1.060 Inches Maximum |
| Outside Diameter: | 1.590 Inches Minimum And 1.637 Inches Maximum |
| Material Thickness: | 0.059 Inches Minimum And 0.067 Inches Maximum |
| Hardness Rating: | 40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum |
| Material: | Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1059 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1064 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Style Designator: | Flat Internal Teeth |
| Nondefinitive Spec/std Data: | 1 Type And A Grade And 1 Style And 1 Composition |

How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-49> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.