

Description

Hole Diameter: 3/8", stainless steel, internal teeth, MS35333 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS3533375 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5310-00-178-8631 |
| Schedule B: | 7318.22.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



P/N MS35333-75 Specifications

| | |
|---|--|
| Hole Diameter: | 0.320 Inches Minimum And 0.332 Inches Maximum |
| Outside Diameter: | 0.594 Inches Minimum And 0.610 Inches Maximum |
| Material Thickness: | 0.028 Inches Minimum And 0.034 Inches Maximum |
| Hardness Rating: | 40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum |
| Material: | Steel Comp 410 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall Or Qq-p-35,ty 3 Fed Spec Single Treatment Response Overall |
| Style Designator: | Flat Internal Teeth |
| Nondefinitive Spec/std Data: | 1 Type And A Grade And 1 Style And 2 Composition |

How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-75> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.