

**Description**

Hole Diameter: 3/8", stainless steel, internal teeth, MS35333 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS3533375
Minimum Qty (MOQ):	100
NSN:	5310-00-178-8631
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



# P/N MS35333-75 Specifications

Hole Diameter:	0.320 Inches Minimum And 0.332 Inches Maximum
Outside Diameter:	0.594 Inches Minimum And 0.610 Inches Maximum
Material Thickness:	0.028 Inches Minimum And 0.034 Inches Maximum
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall Or Qq-p-35,ty 3 Fed Spec Single Treatment Response Overall
Style Designator:	Flat Internal Teeth
Nondefinitive Spec/std Data:	1 Type And A Grade And 1 Style And 2 Composition

## How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35333-75> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.