

Description

fits diameter: 3/8", external teeth, carbon steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS3533535
Minimum Qty (MOQ):	100
NSN:	5310-00-627-6128
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N MS35335-35 Specifications

<b>Hole Diameter:</b>	0.384 Inches Minimum And 0.398 Inches Maximum
<b>Outside Diameter:</b>	0.670 Inches Minimum And 0.694 Inches Maximum
<b>Material Thickness:</b>	0.032 Inches Minimum And 0.040 Inches Maximum
<b>Hardness Rating:</b>	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
<b>Material:</b>	Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1059 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1064 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Flat External Teeth

## How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35335-35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.