

**Description**

Hole Diameter: 25/32",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS3533540
Minimum Qty (MOQ):	25
NSN:	5310-00-275-3683
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

# P/N MS35335-40 Specifications

Hole Diameter:	0.768 Inches Minimum And 0.795 Inches Maximum
Outside Diameter:	1.220 Inches Minimum And 1.260 Inches Maximum
Material Thickness:	0.047 Inches Minimum And 0.055 Inches Maximum
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Material:	Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1059 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1064 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Flat External Teeth
Nondefinitive Spec/std Data:	1 Type And A Grade And 1 Style And 1 Composition

## How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/MS35335-40> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.