

P/N MS35335-59

Description

MS35335-59

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS3533559

Minimum Qty (MOQ): 100

NSN: 5310-00-596-7693

ECCN: EAR99

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,









P/N MS35335-59 Specifications

| Hole Diameter: | 0.168 Inches Minimum And 0.176 Inches Maximum |
|--|--|
| Outside Diameter: | 0.365 Inches Minimum And 0.381 Inches Maximum |
| Material Thickness: | 0.018 Inches Minimum And 0.023 Inches Maximum |
| End Item Identification: | Vehicle, Aircraft Refueler R-14,test Consoles, Mini-sace,test Set, Ttu-205,airborne Mobile Dir Air Spt Ctl (2id),(02m Jul83)(an/uyq-3a), Missile, Airto-air, Phoenix (aim-54),fire Pumps,l.p. Compressors,support Equipment, B-1 Aircraft, Lav, Anti-tank,air Compressors, High Pressure; 2320-01-304-2277 Pls (palletized Loading System) |
| Hardness Rating: | 40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum |
| Material: | Steel Comp 1050 Overall Or Steel Comp 1551 Overall Or Steel Comp 1059 Overall Or Steel Comp 1060 Overall Or Steel Comp 1561 Overall Or Steel Comp 1064 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Style Designator: | Flat External Teeth |

How to Order

Order this lock washer from our inventory online by visiting https://military-fasteners.com/washers/lock+washers/MS35335-59 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.