

P/N MS35335-62

Description

MS35335-62 Lock Washer

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS3533562

Minimum Qty (MOQ): 50

NSN: 5310-00-184-9562

ECCN: EAR99

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,







P/N MS35335-62 Specifications

Hole Diameter:	0.320 Inches Minimum And 0.332 Inches Maximum
Outside Diameter:	0.588 Inches Minimum And 0.610 Inches Maximum
Material Thickness:	0.028 Inches Minimum And 0.034 Inches Maximum
End Item Identification:	W/s: Low Atitute Navigation & Targeting Infrared System (lantirn); Armored Security Vehicle, Model Xm1117; Concolidated Automated Support System (cass); Support Equipment, Mx Peacekeeper Missile; Infantry Carrier; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Teletype, Model 28; Communications Terminal; Engine, Aircraft, F100-pw-100 (f-15a/b/c/d); Spruance Class Dd (963)
Hardness Rating:	40.0 Rockwell C Minimum And 50.0 Rockwell C Maximum
Material:	Steel Comp 410 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 2 Or Ty 3 Fed Spec Single Treatment Response Overall
Style Designator:	Flat External Teeth

How to Order

Order this lock washer from our inventory online by visiting https://military-fasteners.com/washers/lock+washers/MS35335-62 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/lock+washers/MS35335-62 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/lock+washers/MS35335-62 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/lock+washers/MS35335-62 and selecting the quantity you want of the property of the pr